

# Quality Trailers

## GOOSENECK DECKOVER TRAILER – MODEL G

### GENERAL DUTY

- 96" treated wood deck – 101.5" to outside of rubrail
- 8" I-beam frame with 4" flat siderails
- 10" I-beam uprights with 8" I-beam neck
- 3" channel crossmembers – 24" spacing
- 2(5/16)" adjustable gooseneck coupler
- 12,000 lb. drop-foot jack
- Spare tire mount
- Tool tray
- Metal plate over wheels
- Stake pockets with rubrail
- 5' swing-up ramps with support foot
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with conventional wiring and gel-filled connectors
- Primed, painted with acrylic enamel paint, pinstriped



### GVWR – 9,990 lb.

- 5,200 lb. braking axles with double eye suspension
- ST225/75R15 LRE 10 Ply premium Radial tires

### GVWR – 12,000 lb.

- 6,000 lb. braking axles with double eye suspension
- ST235/80R16 LRE 10 Ply Radial tires

### GVWR – 14,000 lb.

- 7,000 lb. braking axles with slipper spring suspension
- ST235/80R16 LRE 10 Ply Radial tires



### STANDARD LENGTHS:

- 20' (16'+4') – 9,990 GVWR
- 24' (20'+4') – 12,000 & 14,000 GVWR
- Shorter Lengths Available

### OPTIONS:

- Tool tray with lockable lid
- Pop-up dovetail
- Cleated dovetail
- No dovetail
- Dual jacks
- Spring-assisted ramps

NOTES:

---

---

---

---