

Quality Trailers

GOOSENECK DECKOVER TRAILER – MODEL G

PROFESSIONAL GRADE

Highlighted Sections Show Spec Upgrades from General Duty Model

- 96" treated wood deck – 101.5" to outside of rubrail
- 2 (5/16)" adjustable gooseneck coupler
- 3" channel crossmembers – 16-17" spacing
- 12,000 lb. drop-foot jack
- Spare tire mount
- Tool tray with lockable lid
- Metal plate over wheels
- Stake pockets with rubrail
- 5' swing-up ramps with support foot
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with sealed modular wiring harness
- Primed, painted with acrylic enamel paint, pinstriped



GVWR – 9,990 lb.

- 8" I-beam frame with 4" flat siderails
- 10" I-beam uprights with 8" I-beam neck
- 5,200 lb. braking axles with double eye suspension
- ST225/75R15 LRE 10 Ply premium Radial tires

GVWR – 12,000 lb.

- 8" I-beam frame with 6" flat siderails
- 10" I-beam uprights with 8" I-beam neck
- 6,000 lb. braking axles with double eye suspension
- ST235/80R16 LRE 10 Ply premium Radial tires

GVWR – 17,000 lb.

- 10" I-beam frame with 6" flat siderails
- 12" I-beam uprights with 10" I-beam neck
- 7,000 lb. braking axles with slipper spring suspension
- Upgraded 4" channel spring-assisted ramps
- ST235/80R16 LRE 10 Ply premium Radial tires



STANDARD LENGTHS:

- 20' (16'+4') – 9,990 GVWR
- 24' (20'+4') – 12,000 & 17,000 GVWR
- 28' (24'+4') – 17,000 GVWR
- Other Lengths Available

OPTIONS:

- 4' pop-up dovetail
- Dual jacks
- ST 235/85R16 LRG 14 Ply premium Radial tires
- 7,500 lb. axles with LRJ tires – 18,000 GVWR
- Lay-flat ramps (only available on lengths 24'+)
- Wood-filled ramps
- Torque Tube

NOTES:
