

# Quality Trailers

## GOOSENECK TANDEM DUAL DECKOVER TRAILER – MODEL HG

### GENERAL DUTY

- 22,000 lb. GVWR
- 96" treated wood deck – 101.5" to outside of rubrail
- 10,000 lb. oil bath axles with electric brakes
- Slipper spring suspension
- 10" I-beam frame with 6" flat siderails
- 12" I-beam uprights with 10" I-beam neck
- 3" channel crossmembers – 24" spacing
- 2(5/16)" adjustable gooseneck coupler
- Spare tire mount
- Single 12,000 lb. drop-foot jack on 24' length
- Dual 12,000 lb. drop-foot jacks on 28' length
- Tool tray
- Metal plate over wheels
- Stake pockets with rubrail
- 6' spring-assisted swing-up ramps with support foot
- ST235/80R16 LRE 10 ply premium Radial tires
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with conventional wiring and gel-filled connectors
- Primed, painted with acrylic enamel paint, pinstriped



### STANDARD LENGTHS:

- 24' (20'+4')
- 28' (24'+4')
- Shorter Lengths Available



### OPTIONS:

- Tool tray with lockable lid
- 4' pop-up dovetail
- Cleated dovetail
- No dovetail
- Lay-flat ramps (only available on lengths 25'+)
- Wood-filled ramps
- Dual speed jacks

### NOTES:

---

---

---

---