

Quality Trailers

GOOSENECK TANDEM DUAL DECKOVER TRAILER – MODEL HG

PROFESSIONAL GRADE

Highlighted Sections Show Spec Upgrades from General Duty Model

- 25,000 lb. GVWR
- 96" treated wood deck – 101.5" to outside of rubrail
- 10,000 lb. oil bath axles with electric brakes
- Slipper spring suspension
- 12" I-beam frame with 6" channel siderails
- 12" I-beam uprights with 12" I-beam neck
- 3" channel crossmembers – 16-17" spacing
- 2 (5/16)" adjustable gooseneck coupler
- Spare tire mount
- Dual 12,000 lb. drop-foot jacks
- Tool tray with lockable lid
- Metal plate over wheels
- Stake pockets with rubrail
- 6' spring-assisted swing-up ramps with support foot
- ST235/80R16 LRE 10 ply premium Radial tires
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with sealed modular wiring harness
- Primed, painted with acrylic enamel paint, pinstriped



STANDARD LENGTHS:

- 25' (20'+5')
- 30' (25'+5')
- Other Lengths Available



OPTIONS:

- Torque Tube
- 4' pop-up dovetail
- Cleated dovetail
- No dovetail
- Lay-flat ramps (only available on lengths 25'+)
- Wood-filled ramps
- Dual speed jacks
- 12" OC crossmember spacing
- Deck on neck

NOTES:
