

Quality Trailers

PINTLE TANDEM DUAL DECKOVER TRAILER – MODEL HP

PROFESSIONAL GRADE

Highlighted Sections Show Spec Upgrades from General Duty Model

- 25,000 lb. GVWR
- 96" treated wood deck – 101.5" to outside of rubrail
- 10,000 lb. oil bath axles with electric brakes
- Slipper spring suspension
- 12" I-beam frame with 6" channel siderails
- Cold form continuous tongue (no notching or heating)
- 3" channel crossmembers – 16-17" spacing
- Adjustable pintle ring
- Spare tire mount
- 12,000 lb. drop-foot jack
- Tool tray with lockable lid
- Metal plate over wheels
- Stake pockets with rubrail
- 6' spring-assisted swing-up ramps with support foot
- ST235/80R16 LRE 10 ply premium Radial tires
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with sealed modular wiring harness
- Primed, painted with acrylic enamel paint, pinstriped



STANDARD LENGTH:

- 25' (20'+5')
- Other Lengths Available



OPTIONS:

- 4' pop-up dovetail
- Cleated dovetail
- Lay-flat ramps (only available on lengths 23'+)
- Wood-filled ramps
- Dual jacks
- Dual speed jacks
- 12" OC crossmember spacing
- Torque Tube

NOTES:
