

Quality Trailers

TANDEM AXLE LANDSCAPE TRAILER – MODEL B

GENERAL DUTY

- Treated wood deck
- 2' dovetail
- 82" between the fenders
- 2 (5/16)" A-frame coupler
- Spare tire mount
- Topwind A-frame jack
- 3" channel and 3 x 3 x 3/16" angle crossmembers
- Double eye spring suspension
- Diamond plate fenders with backs
- Steps front and rear of fenders
- Stake pockets
- 4' spring-assisted landscape gate – 4,500 lb. capacity
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with conventional wiring and gel-filled connectors
- Primed, painted with acrylic enamel paint, pinstriped



GVWR – 7,000 lb.

- 3 x 3 x 3/16" Angle frame with 4" channel wrap-around tongue
- 3 x 3 x 3/16" Angle top rail
- 3,500 lb. braking axles
- ST205/75R15 LRC 6 Ply Radial tires

GVWR – 8,500 lb.

- 3 x 3 x 3/16" Angle frame with 4" channel wrap-around tongue
- 3 x 3 x 3/16" Angle top rail
- 4,400 lb. braking axles
- ST225/75R15 LRD 8 Ply Radial tires



GVWR – 9,990 lb.

- 3 x 3 x 3/16" Angle frame with 5" channel wrap-around tongue
- 3 x 3 x 3/16" Angle top rail
- 5,200 lb. braking axles
- ST225/75R15 LRD 8 Ply Radial tires

STANDARD LENGTHS:

- 14' (12'+2')
- 16' (14'+2')
- 18' (16'+2')
- 20' (18'+2')

NOTES:

OPTIONS:

- Adjustable coupler
- Set Back Topwind Jack
- Swing-up jack
- 7K drop-foot Jack
- ATV side rails