

Quality Trailers

WOOD DECK FENDER EQUIPMENT TRAILER – MODEL DH

GENERAL DUTY

- Treated wood deck
- 2' dovetail
- 6" channel frame
- 3" channel crossmembers – 24" spacing
- 82" between the fenders
- Adjustable 2 (5/16)" coupler or pintle ring
- Spare tire mount
- 7,000 lb. drop-foot jack
- Diamond plate fenders with backs
- Steps front and rear of fenders
- Stake pockets
- 5' swing-up ramps with support foot
- Self-charging breakaway kit, safety chains, and reflective tape
- Rubber mounted sealed beam LED lighting with conventional wiring and gel-filled connectors
- Primed, painted with acrylic enamel paint, pinstriped



GVWR – 9,990 lb.

- 5" channel wrap-around tongue
- 5,200 lb. braking axles with double eye suspension
- ST225/75R15 LRD 8 Ply Radial tires

GVWR – 12,000 lb.

- 6" channel wrap-around tongue
- 6,000 lb. braking axles with double eye suspension
- ST235/80R16 LRE 10 Ply Radial tires

GVWR – 14,000 lb.

- 6" channel wrap-around tongue
- 7,000 lb. braking axles with slipper spring suspension
- ST235/80R16 LRE 10 Ply Radial tires



STANDARD LENGTHS:

- 16' (14'+2')
- 18' (16'+2')
- 20' (18'+2')
- Other Lengths Available

OPTIONS:

- Tool tray with lockable lid
- Cleated dovetail
- No dovetail
- Spring-assisted ramps
- Wood-filled ramps
- Gooseneck

NOTES:
